



screw terminal block 1 level feed-through, 35 mm², grey

Series	CBC
Code	CBC35GR
Type	CBC.35/GR
Colour	grey
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	35 mm ²
Connecting capacity	
Flexible wire	2.5-50 mm ²
Rigid wire	2.5-50 mm ²
Wire with ferrule - ferrule type	35 mm ² - WP350/30
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	
Caliber	B9
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	125 A
Section (min-max)	12-1 (AWG)
Tightening torque value (UL)	75 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	630 V
Maximum current (rated cross-section)	125 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	12 kV / 3
Insulation stripping length	18 mm
Tightening torque value (nom. / max.)	2.5 / 5 Nm
Width (pitch)	16 mm
Length	56 mm
Height mounted on TH35-7.5/TH35-15/G32	63 / 71 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	CBC.35/PT/GR (cod. CB351GR)
Blue	CBC.35/PT (Ex)i (cod. CBI351)
Thickness	1.5 mm
Cross-connection	
Model A)	POF/35 (cod. POF35) - PFX/35 (cod. PFX35)
Model B)	∅
Rated current carrying capacity IEC/ATEX	125 A / 125 A
Cross-connection identification strip	∅
Switchable cross-connection	∅
Multiple cross-connection bar	PMP/35 (cod. PMP35) 16 poles
Shunting screw and sleeve (Standard / Exe)	CPM/35 (cod. CPM35) - CPX/35 (cod. CPX35)
Protection cover	PRP/8 (cod. PRP08)
Coloured partition plate	DFU/5/R (cod. DU05R)
Cross-connection barrier	DFM/700 (cod. DF700)
Test plug and socket	SDD/2 (cod. DD002) - PSD/B (cod. PD002)
Modular test plug	∅
End section for modular test plug	∅
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S)
Single marking tag for pitch insertion	-
Warning plate	TUM/16 (cod. TUM16)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	
         	

