

## Product data sheet

### HDC3330KUE7

#### Characteristics

Contactor, HDC3-330, 2 NC+2 NO, AC/DC 100-250 V, 50 Hz



#### Main

Range of product	HDC3
Product or component type	Contactor
Poles description	3P
[Ith] conventional free air thermal current	380 A

#### Complementary

[In] rated current	330 A
[Uc] control circuit voltage	100...250 V AC 50 Hz
Auxiliary contact composition	2 NO + 2 NC
[Ui] rated insulation voltage	1000 V
Height	201.5 mm
Width	154 mm
Depth	208 mm
Product weight	6.65 kg

#### Environment

Pollution degree	3
Ambient air temperature for operation	-5...40 °C
Average ambient air temperature for operation	= 35 °C (average over 24 hours)
Ambient air temperature for storage	-25...55 °C
Operating altitude	2000 m
Standards	IEC 60947-4-1
Product certifications	CB CE SEMKO
IP degree of protection	IP20
Relative humidity	0...90 %

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	31.5 cm

---

Package 1 Length	54 cm
Package 1 Weight	6.65 kg

---

**Offer Sustainability**

---

Sustainable packaging	No
-----------------------	----

---