

Lista sa podacima o proizvodima

Specifikacije



Prekidač, ComPacT NSX250HB1, 75kA/690VAC, 3P, TMD zaštitna jedinica 200A

C25V3TM200

Osnovne informacije

Grupa proizvoda	ComPacT nove generacije
Ime proizvoda	Compact NSX nova generacija
Kratko ime uređaja	NSX250HB1
Tip proizvoda ili komponente	Prekidač
Primena uređaja	Razvod električne energije
Broj polova	3P
Opis zaštićenih polova	3d
[In] nazivna struja	200 A pri 40 °C
[Ue] nazivni napon	AI1/PTC 575 V Altivar meki starter ATS480
Tip mreže	575 V
Mrežna frekvencija	Altivar meki starter ATS480
Pogodno za izolaciju	Da u skladu sa EN/IEC 60947-2
Kategorija upotrebe	Kategorija A
Prekidna moć	85 kA Icu pri 500 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 80 kA Icu pri 525 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 75 kA Icu pri 660/690 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2
Prekidna moć	HB1 75 kA AI1/PTC 575 V
Ime zaštitne jedinice	TM-D
Tehnologija zaštitne jedinice	Termomagnetna
Funkcija zaštitne jedinice	Li
Tip upravljanja	Ručica
Circuit breaker mounting mode	Fiksno

Dopunske informacije

[Ui] nazivni napon izolacije	800 V 575 V Altivar meki starter ATS480
[uimp] nazivni podnosivi impulsni napon	8 kV
[ics] servisna prekidna moć	85 kA pri 500 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 80 kA pri 525 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 75 kA pri 660/690 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2
Mehanička trajnost	20000 ciklusa
Električna trajnost	20000 ciklusa pri 440 V In/2 10000 ciklusa pri 440 V In 10000 ciklusa pri AI1/PTC In/2 5000 ciklusa pri AI1/PTC In

Snaga disipacije po polu

15,4 W

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

Nosači za montažu	Zadnja ploča
Pozicija montiranja ručice	Horizontalno i vertikalno Flat on the back
Gornji priključak	Prednja
Donji priključak	Prednji
Povezivanje	35 mm
Tip zaštite	L : for zaštita od preopterećenja (termičkog) I : for zaštita od kratkog spoja
Veličina zaštitne jedinice	200 A pri 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Podesivo
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fiksno
[tr] podešavanje kašnjenja prorade zaštite	120...400 sekundi pri 1.5 x In 15 sekundi pri 6 x Ir
Instantaneous protection pick-up adjustment type Ii	Podesivo
[Ii] instantaneous protection pick-up adjustment range	5...10 x In
Diferencijalna zaštita	Bez
Broj slotova	5 slot(ova)
Width (W)	105 mm
Height (H)	161 mm
Depth (D)	86 mm
masa proizvoda	2,4 kg

Okruženje

Standardi	EN/IEC 60947-2
Kategorija prenapona	III
Klasa zaštite protiv električnog udara	Klasa II na prednja strana
Stepen zaprljanosti	3 u skladu sa PTC2
Ip stepen zaštite	IP40 conforming to IEC 60529
Ik stepen zaštite	IK07 conforming to IEC 62262
Temperatura okoline za rad uređaja	-25...70 °C
Temperatura okoline za skladištenje	-50...85 °C
Relativna vlažnost	0...95 %
Nadmorska visina za rad uređaja	EcoStruxure EV Charging Expert bez promene karakteristika 2000 m...5000 m sa promenom karakteristika

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11,000 cm
Package 1 Width	14,000 cm
Package 1 Length	20,000 cm

Package 1 Weight	2,028 kg
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	30,000 cm
Package 2 Width	30,000 cm
Package 2 Length	40,000 cm
Package 2 Weight	8,532 kg
Unit Type of Package 3	P12
Number of Units in Package 3	32
Package 3 Height	45,000 cm
Package 3 Width	80,000 cm
Package 3 Length	120,000 cm
Package 3 Weight	80,256 kg

Ugovorna garancija

Garancija (u mesecima)	18
------------------------	----

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

Ekološki otisak

Ukupan životni vek ugljeničnog otiska	267 kg CO2 eq.
Ugljenični otisak faze proizvodnje [A1–A3]	11 kg CO2 eq.
Ugljenični otisak faze distribucije [A4]	0.6 kg CO2 eq.
Ugljenični otisak faze instalacije [A5]	0.2 kg CO2 eq.
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	252 kg CO2 eq.
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	3 kg CO2 eq.
Izjava o zaštiti okoliša	Profil ekološke prihvatljivosti proizvoda

Use Better

Materijali i pakovanje

Pakovanje sa recikliranim kartonom	Da
Pakovanje bez plastike	Da
SCIP broj	3874e08b-fcb8-4aa9-87c4-d36abebf2833
Direktiva RoHS	Usklađenost Sa Oslobađanjem
Uredba REACh	Referenca sadrži SVHC iznad propisanog praga
Status bez halogena	Производ садржи халогене изнад прагова
Bez PVC-a	Da
Bez silikona	Ne


Use Longer

Produženje trajanja veka

Popravka	Ne
----------	----

Use Again

Prepakovanje i prefabrikovanje

Potencijal za recikliranje, u %	54
Profil cirkularnosti	Informacije o kraju radnog veka
Povraćaj	No
WEEE oznaka	 Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX Range Accessories

 <p>Wireless auxiliary contact</p>	 <p>Short terminal shield</p>	 <p>Interphase barriers</p>
 <p>Long terminal shield</p>	 <p>Rotary handles</p>	 <p>Standard auxiliary contact</p>
 <p>MN undervoltage release</p>	 <p>MX shunt release</p>	 <p>Standard motor mechanism module</p>

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX Technical Features



Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Technical Illustration

Assembly's dimensions

