

# Lista sa podacima o proizvodima

Specifikacije



## Prekidač, ComPacT NSX630H, 70kA/415VAC, 4P, MicroLogic 2.3 zaštitna jedinica 630A

C63H42D630

### Osnovne informacije

Grupa proizvoda	ComPacT nove generacije
Ime proizvoda	Compact NSX nova generacija
Kratko ime uređaja	NSX630H
Tip proizvoda ili komponente	Prekidač
Primena uređaja	Razvod električne energije
Broj polova	4P
Opis zaštićenih polova	4d 3d + N/2 3d
Pozicija nultog provodnika	Levo
[in] nazivna struja	630 A pri 40 °C
[ue] nazivni napon	A11/PTC 575 V Altivar meki starter ATS480
Tip mreže	575 V
Mrežna frekvencija	Altivar meki starter ATS480
Pogodno za izolaciju	Da u skladu sa EN/IEC 60947-2
Kategorija upotrebe	Kategorija A
Prekidna moć	100 kA Icu pri 220/240 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 70 kA Icu pri 380/415 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 65 kA Icu pri 440 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 50 kA Icu pri 500 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 35 kA Icu pri 525 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 20 kA Icu pri 660/690 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 85 kA Icu pri 240 V 575 V Altivar meki starter ATS480 u skladu sa UL 60947-4-1 65 kA Icu pri 480 V 575 V Altivar meki starter ATS480 u skladu sa UL 60947-4-1 20 kA Icu pri 600 V 575 V Altivar meki starter ATS480 u skladu sa UL 60947-4-1
Prekidna moć	H 70 kA 415 V 575 V
Ime zaštitne jedinice	Micrologic 2.3
Tehnologija zaštitne jedinice	Elektronska
Funkcija zaštitne jedinice	LSol
Tip upravljanja	Ručica
Circuit breaker mounting mode	Fiksno

### Dopunske informacije

[ui] nazivni napon izolacije	800 V 575 V Altivar meki starter ATS480
[uimp] nazivni podnosivi impulsni napon	8 kV

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

<b>[ics] servisna prekidna moć</b>	100 kA pri 220/240 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 70 kA pri 380/415 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 65 kA pri 440 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 50 kA pri 500 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 11 kA pri 525 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 10 kA pri 660/690 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2
<b>Mehanička trajnost</b>	15000 ciklusa
<b>Električna trajnost</b>	8000 ciklusa pri 440 V In/2 4000 ciklusa pri 440 V In 6000 ciklusa pri AI1/PTC In/2 2000 ciklusa pri AI1/PTC In
<b>Snaga disipacije po polu</b>	39,7 W
<b>Nosači za montažu</b>	Zadnja ploča
<b>Pozicija montiranja ručice</b>	Horizontalno i vertikalno Flat on the back
<b>Gornji priključak</b>	Prednja
<b>Donji priključak</b>	Prednji
<b>Povezivanje</b>	45 mm
<b>Tip zaštite</b>	L : for zaštita od preopterećenja (dugotrajno) So : for kratkotrajna zaštita od kratkog spoja sa fiksnim kašnjenjem I : for trenutna zaštita od kratkog spoja
<b>Veličina zaštitne jedinice</b>	630 A pri 40 °C
<b>Long-time pick-up adjustment type Ir (thermal protection)</b>	Podesivo 9 podešavanja
<b>[Ir] long-time protection pick-up adjustment range</b>	250...630 A
<b>Long-time protection delay adjustment type tr</b>	Fiksno
<b>[tr] podešavanje kašnjenja prorade zaštite</b>	400 sekundi pri 1.5 x Ir 16 sekundi pri 6 x Ir 11 sekundi pri 7.2 x Ir
<b>Zaštita nultog provodnika</b>	0.5 x Ir (3d + N/2) 1 x Ir (4d) Bez zaštite (3d)
<b>Termička memorija</b>	20 minuta pre i nakon okidanja
<b>Short-time protection pick-up adjustment type Isd</b>	Podesivo, 9 podešavanja
<b>[Isd] Short-time protection pick-up adjustment range</b>	1.5...10 x Ir
<b>Short-time protection delay adjustment type tsd</b>	Fiksno
<b>Instantaneous protection pick-up adjustment type Ii</b>	Fiksno
<b>[Ii] instantaneous protection pick-up adjustment range</b>	6900 A
<b>Diferencijalna zaštita</b>	Bez
<b>Zona selektivne blokade zsi</b>	Bez
<b>Broj slotova</b>	6 slot(ova)
<b>Lokalna signalizacija</b>	Treperi LED (zelena) for uređaj spreman za rad LED 105 % Ir (crvena) for preopterećenje LED 90 % Ir (narandžasta) for preopterećenje
<b>Width (W)</b>	185 mm
<b>Height (H)</b>	255 mm
<b>Depth (D)</b>	110 mm
<b>masa proizvoda</b>	8,13 kg

## Okruženje

Standardi	EN/IEC 60947-2
Kategorija prenapona	III
Klasa zaštite protiv električnog udara	Klasa II na prednja strana
Stepen zaprijanosti	3 u skladu sa PTC2
Ip stepen zaštite	IP40 conforming to IEC 60529
Ik stepen zaštite	IK07 conforming to IEC 62262
Temperatura okoline za rad uređaja	-25...70 °C
Temperatura okoline za skladištenje	-50...85 °C
Relativna vlažnost	0...95 %
Nadmorska visina za rad uređaja	EcoStruxure EV Charging Expert bez promene karakteristika 2000 m...5000 m sa promenom karakteristika

## Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15,000 cm
Package 1 Width	20,400 cm
Package 1 Length	29,000 cm
Package 1 Weight	7,542 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30,000 cm
Package 2 Width	40,000 cm
Package 2 Length	60,000 cm
Package 2 Weight	15,650 kg

## Ugovorna garancija

Garancija (u mesecima)	18
------------------------	----

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

### Ekološki otisak

Ukupan životni vek ugljeničnog otiska	706 kg CO2 eq.
Ugljenični otisak faze proizvodnje [A1–A3]	48 kg CO2 eq.
Ugljenični otisak faze distribucije [A4]	1 kg CO2 eq.
Ugljenični otisak faze instalacije [A5]	0.8 kg CO2 eq.
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	641 kg CO2 eq.
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	15 kg CO2 eq.
Izjava o zaštiti okoliša	<a href="#">Profil ekološke prihvatljivosti proizvoda</a>

### Use Better

#### Materijali i pakovanje

Pakovanje sa recikliranim kartonom	Da
Pakovanje bez plastike	Da
SCIP broj	25ca3248-85d0-423a-a9d8-5b7aeb52e7b6
Direktiva RoHS	<a href="#">Usklađenost Sa Oslobađanjem</a>
Uredba REACh	<a href="#">Referenca sadrži SVHC iznad propisanog praga</a>
Status bez halogena	Производ садржи халогене изнад прагова
Bez PVC-a	Da
Bez silikona	Ne

### Use Longer

#### Produženje trajanja veka

Popravka	Ne
Ažuririvost	Ne

### Use Again

#### Prepakovanje i prefabrikovanje

Potencijal za recikliranje, u %	56
Profil cirkularnosti	<a href="#">Informacije o kraju radnog veka</a>
Povraćaj	No

WEEE oznaka



Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

---

Offer Marketing Illustration

Product benefits / Features

---



Offer Marketing Illustration

Product benefits / Features

---



### ComPacT NSX Range Accessories

 <p data-bbox="172 658 310 701">Wireless auxiliary contact</p>	 <p data-bbox="384 658 548 678">Short terminal shield</p>	 <p data-bbox="622 658 774 678">Interphase barriers</p>
 <p data-bbox="189 831 292 875">Long terminal shield</p>	 <p data-bbox="381 831 561 853">Rotary handles</p>	 <p data-bbox="622 831 767 875">Standard auxiliary contact</p>
 <p data-bbox="172 1010 310 1048">MN undervoltage release</p>	 <p data-bbox="395 1010 534 1032">MX shunt release</p>	 <p data-bbox="622 1010 774 1048">Standard motor mechanism module</p>

Offer Marketing Illustration

Product benefits / Features

---



The image shows a Schneider ComPacT NSX circuit breaker, a black plastic unit with a green handle and internal components. It is positioned on the left side of a white rectangular area, with a large green semi-circle behind it. To the right of the breaker, the text 'ComPacT NSX' is written in a bold, dark grey font, and 'Technical Benefits' is written below it in a green font. A list of six technical benefits follows, each preceded by a green vertical bar.

## ComPacT NSX

### Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

---

## ComPacT NSX Moulded Case Circuit Breaker



### Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



### Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



### Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Technical Illustration

Assembly's dimensions

---

