

Lista sa podacima o proizvodima

Specifikacije

4 stopice - za bakarni kabl 185 mm² i međufazne pregrade



LV429258

Osnovne informacije

Tip proizvoda ili komponente	Stopice
Pribor / posebna kategorija	Pribor za povezivanje
Kompatibilnost grupe proizvoda	ComPacT nova generacija NSX100 ComPacT nova generacija NSX160 ComPacT nova generacija NSX250 ComPacT nova generacija NSX100 DC ComPacT nova generacija NSX160 DC ComPacT nova generacija NSX250 DC EasyPact CVS100...250 Compact INS250 Compact Compact INV100...250 Fupact Fupact ISFT Fupact Fupact INF
Broj polova	4P
Količina po setu	Set od 4
[in] nazivna struja	250 A

Dopunske informacije

Zaštitna oprema	Interphase barriers
Provodni materijal	Bakar
Povezivanje - priključci	Stopica: 1 cable(s) 185 mm ²

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,0 cm
Package 1 Width	11,0 cm
Package 1 Length	11,5 cm
Package 1 Weight	434,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	10,5 cm
Package 2 Width	19,8 cm
Package 2 Length	35,5 cm
Package 2 Weight	5,403 kg
Unit Type of Package 3	S03

Number of Units in Package 3

24

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	10,8 kg

Ugovorna garancija

Garancija (u mesecima)	18
------------------------	----

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

Ekološki otisak

Ukupan životni vek ugljeničnog otiska	3 kg CO2 eq.
Ugljenični otisak faze proizvodnje [A1–A3]	2 kg CO2 eq.
Ugljenični otisak faze distribucije [A4]	0.1 kg CO2 eq.
Ugljenični otisak faze instalacije [A5]	0 kg CO2 eq.
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	0 kg CO2 eq.
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	0.8 kg CO2 eq.
Izjava o zaštiti okoliša	Profil ekološke prihvatljivosti proizvoda

Use Better

Materijali i pakovanje

Pakovanje sa recikliranim kartonom	Da
Pakovanje bez plastike	Ne
Direktiva RoHS	Usaglašeno
Uredba REACH	Referenca ne sadrži SVHC iznad propisanog praga
Status bez halogena	Производ садржи халогене изнад прагова

Use Longer

Produženje trajanja veka

Popravka	Ne
----------	----

Use Again

Prepakovanje i prefabrikovanje

Potencijal za recikliranje, u %	83
Profil cirkularnosti	Nema potrebe za namenskim operacijama recikliranja
Povraćaj	No

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

