


Lista sa podacima o proizvodima

Specifikacije



varistor - 24..60 V AC/DC - za RPZ/ RXZ podnožja

RXM021BN

Osnovne informacije

Grupa proizvoda	Harmony Electromechanical Relays
Pribor / posebna kategorija	Pribor za zaštitu
Tip proizvoda ili komponente	Zaštitni modul
Pribor / posebna namena	Varistor
Kompatibilnost proizvoda	Utičnica RPZ (1 C/O) Utičnica RPZ (2 C/O) Utičnica RXZ (2 C/O) Utičnica RXZ (3 C/O) Utičnica RXZ (4 C/O)
Namena proizvoda	RXM relej RPM relej
Napon upravljačkog kola	24...60 V AC/DC
Prodaja po nedeljivim količinama	20

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,300 cm
Package 1 Width	1,400 cm
Package 1 Length	3,200 cm
Package 1 Weight	1,800 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1,500 cm
Package 2 Width	6,000 cm
Package 2 Length	8,000 cm
Package 2 Weight	19,000 g
Unit Type of Package 3	S01
Number of Units in Package 3	500
Package 3 Height	15,000 cm
Package 3 Width	15,000 cm
Package 3 Length	40,000 cm
Package 3 Weight	1,218 kg

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

Ugovorna garancija

Garancija (u mesecima)

18

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

Ekološki otisak

Ukupan životni vek ugljeničnog otiska	0 kg CO2 eq.
Ugljenični otisak faze proizvodnje [A1–A3]	0 kg CO2 eq.
Ugljenični otisak faze distribucije [A4]	0 kg CO2 eq.
Ugljenični otisak faze instalacije [A5]	0 kg CO2 eq.
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	0 kg CO2 eq.
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	0 kg CO2 eq.
Izjava o zaštiti okoliša	Profil ekološke prihvatljivosti proizvoda

Use Better

Materijali i pakovanje

Pakovanje sa recikliranim kartonom	Da
Pakovanje bez plastike	Ne
Direktiva RoHS	Usaglašeno
Uredba REACH	Referenca ne sadrži SVHC iznad propisanog praga

Use Longer

Produženje trajanja veka

Popravka	Ne
----------	----


Use Again

Prepakovanje i prefabrikovanje

Profil cirkularnosti	Nema potrebe za namenskim operacijama recikliranja
Povraćaj	No

Connections and Schema

Wiring Diagram




Offer Marketing Illustration


Product benefits / Features

Features


Harmony RXMAB Relay




Pluggable relay module for easy replacement and retrofitting of relays




Conforms to international standards: IEC, CE, UL, CSA, EAC, Lloyd's, RoHS and REACH





Save time and cost with pre-assembled relays and push-in sockets



Add-on protection modules and timer relay for flexibility

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony RXMAB Relay

RXM*AB sockets:

- Mixed or separate contact arrangement
- Push-in, screw clamp or screw connector terminal

Plastic or metal maintaining clamp to protect against vibration

RXM*AB relays:

- 2CO-12A, 3CO-10A, 4CO-6A
- 12-220VDC, 24-240VAC

Push button (Blue for DC, Red for AC) and lockable test button for contact testing

Mechanical indicator for relay contact status

"Power On" LED for relay status



Image of product / Alternate images

Alternative





