

Lista sa podacima o proizvodima

Specifikacije



Prekidač, ComPacT NSX400N, 50kA/415VAC, 3P, MicroLogic 1.3M zaštitna jedinica 320A

C40N31M320

Osnovne informacije

Grupa proizvoda	ComPacT nove generacije
Ime proizvoda	Compact NSX nova generacija
Kratko ime uređaja	NSX400N
Tip proizvoda ili komponente	Prekidač
Primena uređaja	Zaštita motora
Broj polova	3P
Opis zaštićenih polova	3d
[in] nazivna struja	320 A pri 65 °C
[ue] nazivni napon	A11/PTC 575 V Altivar meki starter ATS480
Tip mreže	575 V
Mrežna frekvencija	Altivar meki starter ATS480
Pogodno za izolaciju	Da u skladu sa EN/IEC 60947-2
Kategorija upotrebe	Kategorija A
Prekidna moć	85 kA Icu pri 220/240 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 50 kA Icu pri 380/415 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 42 kA Icu pri 440 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 30 kA Icu pri 500 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 22 kA Icu pri 525 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 10 kA Icu pri 660/690 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 85 kA Icu pri 240 V 575 V Altivar meki starter ATS480 u skladu sa UL 60947-4-1 50 kA Icu pri 480 V 575 V Altivar meki starter ATS480 u skladu sa UL 60947-4-1 20 kA Icu pri 600 V 575 V Altivar meki starter ATS480 u skladu sa UL 60947-4-1
Prekidna moć	N 50 kA 415 V 575 V
Ime zaštitne jedinice	Micrologic 1.3 M
Tehnologija zaštitne jedinice	Elektronska
Funkcija zaštitne jedinice	SI
Tip upravljanja	Ručica
Circuit breaker mounting mode	Fiksno

Dopunske informacije

[ui] nazivni napon izolacije	800 V 575 V Altivar meki starter ATS480
[uimp] nazivni podnosivi impulsni napon	8 kV
[ics] servisna prekidna moć	85 kA pri 220/240 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 50 kA pri 380/415 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 42 kA pri 440 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 30 kA pri 500 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 11 kA pri 525 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2 10 kA pri 660/690 V 575 V Altivar meki starter ATS480 u skladu sa IEC 60947-2

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

Mehanička trajnost	15000 ciklusa
Električna trajnost	12000 ciklusa pri 440 V In/2 6000 ciklusa pri 440 V In 6000 ciklusa pri AI1/PTC In/2 3000 ciklusa pri AI1/PTC In
Snaga disipacije po polu	12,29 W
Nosači za montažu	Zadnja ploča
Pozicija montiranja ručice	Horizontalno i vertikalno Flat on the back
Gornji priključak	Prednja
Donji priključak	Prednji
Povezivanje	45 mm
Tip zaštite	S : for kratkotrajna zaštita od kratkog spoja I : for trenutna zaštita od kratkog spoja
Veličina zaštitne jedinice	320 A pri 65 °C
Short-time protection pick-up adjustment type Isd	Podesivo, 9 podešavanja
[Isd] Short-time protection pick-up adjustment range	1600 A 1920 A 2440 A 2560 A 2880 A 3200 A 3520 A 3840 A 4160 A
Short-time protection delay adjustment type tsd	Fiksno
Instantaneous protection pick-up adjustment type Ii	Fiksno
[Ii] instantaneous protection pick-up adjustment range	4800 A
Diferencijalna zaštita	Bez
Zona selektivne blokade zsi	Bez
Broj slotova	6 slot(ova)
Lokalna signalizacija	Treperi LED (zeleni) for uređaj spreman za rad
Width (W)	140 mm
Height (H)	255 mm
Depth (D)	110 mm
masa proizvoda	6,05 kg

Okruženje

Standardi	EN/IEC 60947-2
Kategorija prenapona	III
Klasa zaštite protiv električnog udara	Klasa II na prednja strana
Stepen zaprljanosti	3 u skladu sa PTC2
Ip stepen zaštite	IP40 conforming to IEC 60529
Ik stepen zaštite	IK07 conforming to IEC 62262
Temperatura okoline za rad uređaja	-25...70 °C
Temperatura okoline za skladištenje	-50...85 °C

Relativna vlažnost	0...95 %
--------------------	----------

Nadmorska visina za rad uređaja	EcoStruxure EV Charging Expert bez promene karakteristika 2000 m...5000 m sa promenom karakteristika
---------------------------------	---

Pakovanje

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	15,200 cm
------------------	-----------

Package 1 Width	15,500 cm
-----------------	-----------

Package 1 Length	29,200 cm
------------------	-----------

Package 1 Weight	5,588 kg
------------------	----------

Unit Type of Package 2	S04
------------------------	-----

Number of Units in Package 2	2
------------------------------	---

Package 2 Height	30,000 cm
------------------	-----------

Package 2 Width	40,000 cm
-----------------	-----------

Package 2 Length	60,000 cm
------------------	-----------

Package 2 Weight	11,761 kg
------------------	-----------

Ugovorna garancija

Garancija (u mesecima)	18
------------------------	----

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

[Objašnjeni Environmental Data >](#)

[Kako procenjujemo održivost proizvoda >](#)

Ekološki otisak

Ukupan životni vek ugljeničnog otiska	246 kg CO2 eq.
Ugljenični otisak faze proizvodnje [A1–A3]	35 kg CO2 eq.
Ugljenični otisak faze distribucije [A4]	0.9 kg CO2 eq.
Ugljenični otisak faze instalacije [A5]	0.6 kg CO2 eq.
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	199 kg CO2 eq.
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	11 kg CO2 eq.
Izjava o zaštiti okoliša	Profil ekološke prihvatljivosti proizvoda

Use Better

Materijali i pakovanje

Pakovanje sa recikliranim kartonom	Da
Pakovanje bez plastike	Da
SCIP broj	25ca3248-85d0-423a-a9d8-5b7aeb52e7b6
Direktiva RoHS	Usklađenost Sa Oslobađanjem
Uredba REACh	Referenca sadrži SVHC iznad propisanog praga
Status bez halogena	Производ садржи халогене изнад прагова
Bez PVC-a	Da
Bez silikona	Ne


Use Longer

Produženje trajanja veka

Popravka	Ne
----------	----

Use Again

Prepakovanje i prefabrikovanje

Potencijal za recikliranje, u %	56
Profil cirkularnosti	Informacije o kraju radnog veka
Povraćaj	No
WEEE oznaka	 Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



ComPacT NSX Range Accessories

 <p>Wireless auxiliary contact</p>	 <p>Short terminal shield</p>	 <p>Interphase barriers</p>
 <p>Long terminal shield</p>	 <p>Rotary handles</p>	 <p>Standard auxiliary contact</p>
 <p>MN undervoltage release</p>	 <p>MX shunt release</p>	 <p>Standard motor mechanism module</p>

Offer Marketing Illustration

Product benefits / Features



ComPacT NSX

Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

